

powerBOX[®]

SBW-208-80K

THREE-PHASE
80kVA



SBW-208-80K

THREE-PHASE
80kVA



SPECIFICATIONS

The Stabilizer Specification

Model: SBW-80KW

Input voltage	3-Phase: input: $208V \pm 20\%$ (L-L); with neutral
Output voltage	3-Phase: $208V \pm 2\%$
Output accuracy	$\pm 2\%$
Frequency	60Hz
Capacity:	80KVA PF=1.0
Insulation resistance	$\geq 20M \Omega$
Noise	<55dB
Voltage regulation mode	Independent phase regulation
Wave deformation	Nil
Display	LCD display
Insulation class of transformer	H class
Wire system	3-phase-5-wire-system
Operation time	$\geq 80,000$ hours
The number of carbon brush abrasion	140,000 times with only about 0.01mm roller carbon brush abrasion
Method of voltage regulation	Regulation transformer with servomotor
Insulated strength	Three phase: 2500V/1 min without puncture
Material of package	Carton for batch volume, wooden packing for small volume
Efficiency	>98%
Protection class	IP20
Electrical safety	CE equivalent
Dimension(W*D*H)mm	$400 \times 1000 \times 1680$
Weight	276Kg
Ambient temperature operating	-20 ° C to +45 ° C
Altitude	<1000m
Relative humidity	<90%
Functions	Malfunction protection, Short-circuit protection, Over voltage shutdown, Under voltage shutdown, Safe start; Static independent bypass line and external manual bypass.